

AD-A193 613

ADA (TRADE NAME) COMPILER VALIDATION SUMMARY REPORT

1/1

TELESOFT TELEGEN2 AD (U) INFORMATION SYSTEMS AND


TECHNOLOGY CENTER W-P AFB OH ADA VALI 19 MAR 88


UNCLASSIFIED

AVF-VSR-66 8587

F/G 12/5

NL





MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS 1963 A

AD-A193 613

AVF Control Number: AVF-VSR-66.0587
87-01-21-TEL

DTIC FILE COPY

Ada[®] COMPILER
VALIDATION SUMMARY REPORT:
TeleSoft
TeleGen2 Ada Compiler for VAX/VMS to 1750A, Release 3.12c
MicroVAX II Host and ECSP0 SIM50A Target

Completion of On-Site Testing:
19 March 1987

Prepared By:
Ada Validation Facility
ASD/SCOL
Wright-Patterson AFB OH 45433-6503

Prepared For:
Ada Joint Program Office
United States Department of Defense
Washington, D.C.

DTIC
ELECTE
MAR 28 1988
S H D

©Ada is a registered trademark of the United States Government
(Ada Joint Program Office).

DISTRIBUTION STATEMENT A

Approved for public release;
Distribution Unlimited

88 3 28 030

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE

1. REPORT NUMBER	12. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and subtitle)	Ada Compiler Validation Summary Report: Telesoft Telegen2 Ada Compiler for VAX/VMS to 1750A, Release 3.12c MicroVAX II Host and ECSP0 SIM50A Target	5. TYPE OF REPORT & PERIOD COVERED 19 March '87 to 19 March '88
7. AUTHOR(s)	Wright-Patterson AFB OH 45433-6503	6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION AND ADDRESS	Wright-Patterson AFB OH 45433-6503	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS	Ada Joint Program Office United States Department of Defense Washington, DC 20301-3081ASD/SIOL	12. REPORT DATE 19 March 1987
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	Wright-Patterson AFB OH 45433-6503.	13. NUMBER OF PAGES 32 p.
15. SECURITY CLASS (of this report)	UNCLASSIFIED	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE N/A

16. DISTRIBUTION STATEMENT (of this Report)
Approved for public release; distribution unlimited.

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20. If different from Report)

UNCLASSIFIED

18. SUPPLEMENTARY NOTES

19. KEYWORDS (Continue on reverse side if necessary and identify by block number)

Ada Programming Language, Ada Compiler Validation Summary Report, Ada
Compiler Validation Capability, ACVC, Validation Testing, Ada
Validation Office, AVO, Ada Validation Facility, AVF, ANSI/MIL-STD-
1815A, Ada Joint Program Office, AJPO

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

See Attached.

DD FORM

1473

EDITION OF 1 NOV 65 IS OBSOLETE

S/N 0102-LF-014-6601

1 JAN 73

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

+++++
+
+ Place NTIS form here +
+
+++++

Ada® Compiler Validation Summary Report:

Compiler Name: TeleGen2 Ada Compiler for VAX/VMS to 1750A, Release 3.12c

Host: MicroVAX II under Target: ECSP0 SIM50A (bare)
MicroVMS, Version 4.2 Version 4.0

Testing Completed 19 March 1987 Using ACVC 1.8

This report has been reviewed and is approved.

Steven P. Wilson
Ada Validation Facility
Steven P. Wilson
ASD/SCOL
Wright-Patterson AFB OH 45433-6503

John F. Kramer
Ada Validation Organization
Dr. John F. Kramer
Institute for Defense Analyses
Alexandria VA

Virginia L. Castor
Ada Joint Program Office
Virginia L. Castor
Director
Department of Defense
Washington DC

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

®Ada is a registered trademark of the United States Government
(Ada Joint Program Office).

EXECUTIVE SUMMARY

This Validation Summary Report (VSR) summarizes the results and conclusions of validation testing performed on the TeleGen2 Ada Compiler for VAX/VMS to 1750A, Release 3.12c, using Version 1.8 of the Ada[®] Compiler Validation Capability (ACVC). The TeleGen2 Ada Compiler for VAX/VMS to 1750A is hosted on a MicroVAX II operating under MicroVMS, Version 4.2. Programs processed by this compiler may be executed on an ECSPO SIM50A, Version 4.0.

On-site testing was performed 14 March 1987 through 19 March 1987 at TeleSoft in San Diego CA, under the direction of the Ada Validation Facility (AVF), according to Ada Validation Organization (AVO) policies and procedures. The AVF identified 1974 of the 2399 tests in ACVC Version 1.8 to be processed during on-site testing of the compiler. The 19 tests withdrawn at the time of validation testing, the 242 executable tests that make use of floating-point precision exceeding that supported by the implementation, and the 164 tests that require use of external files not supported by the implementation were not processed. After the 1974 tests were processed, results for Class A, C, D, and E tests were examined for correct execution. Compilation listings for Class B tests were analyzed for correct diagnosis of syntax and semantic errors. Compilation and link results of Class L tests were analyzed for correct detection of errors. There were 39 of the processed tests determined to be inapplicable. The remaining 1935 tests were passed.

The results of validation are summarized in the following table:

RESULT	CHAPTER												TOTAL
	2	3	4	5	6	7	8	9	10	11	12	14	
Passed	96	222	298	242	159	97	136	262	107	32	217	67	1935
Failed	0	0	0	0	0	0	0	0	0	0	0	0	0
Inapplicable	20	103	122	5	2	0	3	0	23	0	1	166	445
Withdrawn	0	5	5	0	0	1	1	2	4	0	1	0	19
TOTAL	116	330	425	247	161	98	140	264	134	32	219	233	2399

The AVF concludes that these results demonstrate acceptable conformity to ANSI/MIL-STD-1815A Ada.

[®]Ada is a registered trademark of the United States Government (Ada Joint Program Office).

TABLE OF CONTENTS

CHAPTER 1	INTRODUCTION	
1.1	PURPOSE OF THIS VALIDATION SUMMARY REPORT	1-2
1.2	USE OF THIS VALIDATION SUMMARY REPORT	1-2
1.3	REFERENCES	1-3
1.4	DEFINITION OF TERMS	1-3
1.5	ACVC TEST CLASSES	1-4
CHAPTER 2	CONFIGURATION INFORMATION	
2.1	CONFIGURATION TESTED	2-1
2.2	IMPLEMENTATION CHARACTERISTICS	2-2
CHAPTER 3	TEST INFORMATION	
3.1	TEST RESULTS	3-1
3.2	SUMMARY OF TEST RESULTS BY CLASS	3-1
3.3	SUMMARY OF TEST RESULTS BY CHAPTER	3-2
3.4	WITHDRAWN TESTS	3-2
3.5	INAPPLICABLE TESTS	3-2
3.6	SPLIT TESTS	3-4
3.7	ADDITIONAL TESTING INFORMATION	3-5
3.7.1	Prevalidation	3-5
3.7.2	Test Method	3-5
3.7.3	Test Site	3-6
APPENDIX A	DECLARATION OF CONFORMANCE	
APPENDIX B	APPENDIX F OF THE Ada STANDARD	
APPENDIX C	TEST PARAMETERS	
APPENDIX D	WITHDRAWN TESTS	

CHAPTER 1

INTRODUCTION

This Validation Summary Report (VSR) describes the extent to which a specific Ada compiler conforms to the Ada Standard, ANSI/MIL-STD-1815A. This report explains all technical terms used within it and thoroughly reports the results of testing this compiler using the Ada Compiler Validation Capability (ACVC). An Ada compiler must be implemented according to the Ada Standard, and any implementation-dependent features must conform to the requirements of the Ada Standard. The Ada Standard must be implemented in its entirety, and nothing can be implemented that is not in the Standard.

Even though all validated Ada compilers conform to the Ada Standard, it must be understood that some differences do exist between implementations. The Ada Standard permits some implementation dependencies--for example, the maximum length of identifiers or the maximum values of integer types. Other differences between compilers result from characteristics of particular operating systems, hardware, or implementation strategies. All of the dependencies observed during the process of testing this compiler are given in this report.

The information in this report is derived from the test results produced during validation testing. The validation process includes submitting a suite of standardized tests, the ACVC, as inputs to an Ada compiler and evaluating the results. The purpose of validating is to ensure conformity of the compiler to the Ada Standard by testing that the compiler properly implements legal language constructs and that it identifies and rejects illegal language constructs. The testing also identifies behavior that is implementation dependent but permitted by the Ada Standard. Six classes of tests are used. These tests are designed to perform checks at compile time, at link time, and during execution.

INTRODUCTION

1.1 PURPOSE OF THIS VALIDATION SUMMARY REPORT

This VSR documents the results of the validation testing performed on an Ada compiler. Testing was carried out for the following purposes:

- . To attempt to identify any language constructs supported by the compiler that do not conform to the Ada Standard
- . To attempt to identify any unsupported language constructs required by the Ada Standard
- . To determine that the implementation-dependent behavior is allowed by the Ada Standard

Testing of this compiler was conducted by SofTech, Inc., under the direction of the AVF according to policies and procedures established by the Ada Validation Organization (AVO). On-site testing was conducted from 14 March 1987 through 19 March 1987 at TeleSoft in San Diego CA.

1.2 USE OF THIS VALIDATION SUMMARY REPORT

Consistent with the national laws of the originating country, the AVO may make full and free public disclosure of this report. In the United States, this is provided in accordance with the "Freedom of Information Act" (5 U.S.C. #552). The results of this validation apply only to the computers, operating systems, and compiler versions identified in this report.

The organizations represented on the signature page of this report do not represent or warrant that all statements set forth in this report are accurate and complete, or that the subject compiler has no nonconformities to the Ada Standard other than those presented. Copies of this report are available to the public from:

Ada Information Clearinghouse
Ada Joint Program Office
OUSDRE
The Pentagon, Rm 3D-130 (Fern Street)
Washington DC 20301-3081

or from:

Ada Validation Facility
ASD/SCOL
Wright-Patterson AFB OH 45433-6503

Questions regarding this report or the validation test results should be directed to the AVF listed above or to:

Ada Validation Organization
Institute for Defense Analyses
1801 North Beauregard Street
Alexandria VA 22311

1.3 REFERENCES

1. Reference Manual for the Ada Programming Language, ANSI/MIL-STD-1815A, FEB 1983.
2. Ada Validation Organization: Procedures and Guidelines, Ada Joint Program Office, 1 JAN 1987.
3. Ada Compiler Validation Capability Implementers' Guide, SofTech, Inc., DEC 1984.

1.4 DEFINITION OF TERMS

ACVC	The Ada Compiler Validation Capability. A set of programs that evaluates the conformity of a compiler to the Ada language specification, ANSI/MIL-STD-1815A.
Ada Standard	ANSI/MIL-STD-1815A, February 1983.
Applicant	The agency requesting validation.
AVF	The Ada Validation Facility. In the context of this report, the AVF is responsible for conducting compiler validations according to established policies and procedures.
AVO	The Ada Validation Organization. In the context of this report, the AVO is responsible for setting procedures for compiler validations.
Compiler	A processor for the Ada language. In the context of this report, a compiler is any language processor, including cross-compilers, translators, and interpreters.
Failed test	A test for which the compiler generates a result that demonstrates nonconformity to the Ada Standard.
Host	The computer on which the compiler resides.

INTRODUCTION

Inapplicable test	A test that uses features of the language that a compiler is not required to support or may legitimately support in a way other than the one expected by the test.
Passed test	A test for which a compiler generates the expected result.
Target	The computer for which a compiler generates code.
Test	A program that checks a compiler's conformity regarding a particular feature or features to the Ada Standard. In the context of this report, the term is used to designate a single test, which may comprise one or more files.
Withdrawn test	A test found to be incorrect and not used to check conformity to the Ada language specification. A test may be incorrect because it has an invalid test objective, fails to meet its test objective, or contains illegal or erroneous use of the language.

1.5 ACVC TEST CLASSES

Conformity to the Ada Standard is measured using the ACVC. The ACVC contains both legal and illegal Ada programs structured into six test classes: A, B, C, D, E, and L. The first letter of a test name identifies the class to which it belongs. Class A, C, D, and E tests are executable, and special program units are used to report their results during execution. Class B tests are expected to produce compilation errors. Class L tests are expected to produce link errors.

Class A tests check that legal Ada programs can be successfully compiled and executed. However, no checks are performed during execution to see if the test objective has been met. For example, a Class A test checks that reserved words of another language (other than those already reserved in the Ada language) are not treated as reserved words by an Ada compiler. A Class A test is passed if no errors are detected at compile time and the program executes to produce a PASSED message.

Class B tests check that a compiler detects illegal language usage. Class B tests are not executable. Each test in this class is compiled and the resulting compilation listing is examined to verify that every syntax or semantic error in the test is detected. A Class B test is passed if every illegal construct that it contains is detected by the compiler.

Class C tests check that legal Ada programs can be correctly compiled and executed. Each Class C test is self-checking and produces a PASSED, FAILED, or NOT APPLICABLE message indicating the result when it is executed.

Class D tests check the compilation and execution capacities of a compiler. Since there are no capacity requirements placed on a compiler by the Ada Standard for some parameters--for example, the number of identifiers

permitted in a compilation or the number of units in a library--a compiler may refuse to compile a Class D test and still be a conforming compiler. Therefore, if a Class D test fails to compile because the capacity of the compiler is exceeded, the test is classified as inapplicable. If a Class D test compiles successfully, it is self-checking and produces a PASSED or FAILED message during execution.

Each Class E test is self-checking and produces a NOT APPLICABLE, PASSED, or FAILED message when it is compiled and executed. However, the Ada Standard permits an implementation to reject programs containing some features addressed by Class E tests during compilation. Therefore, a Class E test is passed by a compiler if it is compiled successfully and executes to produce a PASSED message, or if it is rejected by the compiler for an allowable reason.

Class L tests check that incomplete or illegal Ada programs involving multiple, separately compiled units are detected and not allowed to execute. Class L tests are compiled separately and execution is attempted. A Class L test passes if it is rejected at link time--that is, an attempt to execute the main program must generate an error message before any declarations in the main program or any units referenced by the main program are elaborated.

Two library units, the package REPORT and the procedure CHECK_FILE, support the self-checking features of the executable tests. The package REPORT provides the mechanism by which executable tests report PASSED, FAILED, or NOT APPLICABLE results. It also provides a set of identity functions used to defeat some compiler optimizations allowed by the Ada Standard that would circumvent a test objective. The procedure CHECK_FILE is used to check the contents of text files written by some of the Class C tests for chapter 14 of the Ada Standard. The operation of these units is checked by a set of executable tests. These tests produce messages that are examined to verify that the units are operating correctly. If these units are not operating correctly, then the validation is not attempted.

The text of the tests in the ACVC follow conventions that are intended to ensure that the tests are reasonably portable without modification. For example, the tests make use of only the basic set of 55 characters, contain lines with a maximum length of 72 characters, use small numeric values, and place features that may not be supported by all implementations in separate tests. However, some tests contain values that require the test to be customized according to implementation-specific values--for example, an illegal file name. A list of the values used for this validation is provided in Appendix C.

A compiler must correctly process each of the tests in the suite and demonstrate conformity to the Ada Standard by either meeting the pass criteria given for the test or by showing that the test is inapplicable to the implementation. Any test that was determined to contain an illegal language construct or an erroneous language construct is withdrawn from the ACVC and, therefore, is not used in testing a compiler. The tests withdrawn at the time of validation are given in Appendix D.

CHAPTER 2
CONFIGURATION INFORMATION

2.1 CONFIGURATION TESTED

The candidate compilation system for this validation was tested under the following configuration:

Compiler: TeleGen2 Ada Compiler for VAX/VMS to 1750A, Release 3.12c

ACVC Version: 1.8

Certificate Expiration Date: 2 April 1988

Host Computer:

Machine:	MicroVAX II
Operating System:	MicroVMS, Version 4.2
Memory Size:	10 megabytes

Target Computer:

Machine:	ECSP0 SIM50A, Version 4.0
Operating System:	bare
Memory Size:	64K words

2.2 IMPLEMENTATION CHARACTERISTICS

One of the purposes of validating compilers is to determine the behavior of a compiler in those areas of the Ada Standard that permit implementations to differ. Class D and E tests specifically check for such implementation differences. However, tests in other classes also characterize an implementation. This compiler is characterized by the following interpretations of the Ada Standard:

- . Capacities.

The compiler correctly processes tests containing loop statements nested to 65 levels, block statements nested to 65 levels, and recursive procedures separately compiled as subunits nested to 6 levels. It correctly processes a compilation containing 723 variables in the same declarative part. (See tests D55A03A..H (8 tests), D56001B, D64005E..G (3 tests), and D29002K.)

- . Universal integer calculations.

An implementation is allowed to reject universal integer calculations having values that exceed `SYSTEM.MAX_INT`. This implementation does not reject such calculations and processes them correctly. (See tests D4A002A, D4A002B, D4A004A, and D4A004B.)

- . Predefined types.

This implementation supports the additional predefined types `LONG_INTEGER` and `LONG_FLOAT` in the package `STANDARD`. (See tests B86001C and B86001D.)

- . Based literals.

An implementation is allowed to reject a based literal with a value exceeding `SYSTEM.MAX_INT` during compilation, or it may raise `NUMERIC_ERROR` or `CONSTRAINT_ERROR` during execution. This implementation raises `NUMERIC_ERROR` during execution. (See test E24101A.)

- . Array types.

An implementation is allowed to raise `NUMERIC_ERROR` or `CONSTRAINT_ERROR` for an array having a `'LENGTH` that exceeds `STANDARD.INTEGER'LAST` and/or `SYSTEM.MAX_INT`.

A packed BOOLEAN array having a 'LENGTH exceeding INTEGER'LAST raises NUMERIC_ERROR when the array type is declared. (See test C52103X.)

A packed two-dimensional BOOLEAN array with more than INTEGER'LAST components raises NUMERIC_ERROR when the array types are declared. (See test C52104Y.)

A null array with one dimension of length greater than INTEGER'LAST may raise NUMERIC_ERROR or CONSTRAINT_ERROR either when declared or assigned. Alternatively, an implementation may accept the declaration. However, lengths must match in array slice assignments. This implementation raises NUMERIC_ERROR when the array type is declared. (See test E52103Y.)

In assigning one-dimensional array types, the expression appears to be evaluated in its entirety before CONSTRAINT_ERROR is raised when checking whether the expression's subtype is compatible with the target's subtype. In assigning two-dimensional array types, the expression does not appear to be evaluated in its entirety before CONSTRAINT_ERROR is raised when checking whether the expression's subtype is compatible with the target's subtype. (See test C52013A.)

- . Discriminated types.

During compilation, an implementation is allowed to either accept or reject an incomplete type with discriminants that is used in an access type definition with a compatible discriminant constraint. This implementation accepts such subtype indications. (See test E38104A.)

In assigning record types with discriminants, the expression appears to be evaluated in its entirety before CONSTRAINT_ERROR is raised when checking whether the expression's subtype is compatible with the target's subtype. (See test C52013A.)

- . Aggregates.

In the evaluation of a multi-dimensional aggregate, the order in which choices are evaluated and index subtype checks are made appears to depend upon the aggregate itself. (See tests C43207A and C43207B.)

In the evaluation of an aggregate containing subaggregates, all choices are not evaluated before being checked for identical bounds. (See test E43212B.)

All choices are evaluated before CONSTRAINT_ERROR is raised if a bound in a nonnull range of a nonnull aggregate does not belong to an index subtype. (See test E43211B.)

CONFIGURATION INFORMATION

. Functions.

An implementation may allow the declaration of a parameterless function and an enumeration literal having the same profile in the same immediate scope, or it may reject the function declaration. If it accepts the function declaration, the use of the enumeration literal's identifier denotes the function. This implementation rejects the declaration. (See test E66001D.)

. Representation clauses.

The Ada Standard does not require an implementation to support representation clauses. If a representation clause is not supported, then the implementation must reject it. While the operation of representation clauses is not checked by Version 1.8 of the ACVC, they are used in testing other language features. This implementation accepts 'SIZE and 'SMALL clauses; it rejects 'STORAGE_SIZE for access types. Enumeration representation clauses, including those that specify noncontiguous values, appear not to be supported. (See tests C55B16A, C87B62A, C87B62B, C87B62C, and BC1002A.)

. Pragmas.

The pragma `INLINE` is not supported for procedures or functions. (See tests CA3004E and CA3004F.)

. Input/output.

This implementation supports only the package `TEXT_IO` for file operations on `STANDARD_INPUT` and `STANDARD_OUTPUT`.

The package `SEQUENTIAL_IO` cannot be instantiated with unconstrained array types and record types with discriminants. The package `DIRECT_IO` cannot be instantiated with unconstrained array types and record types with discriminants without defaults. (See tests AE2101C, AE2101H, CE2201D, CE2201E, and CE2401D.)

. Generics.

Generic subprogram declarations and bodies cannot be compiled in separate compilations. (See test CA2009F.)

Generic package declarations and bodies cannot be compiled in separate compilations. (See tests CA2009C and BC3205D.)

CHAPTER 3

TEST INFORMATION

3.1 TEST RESULTS

Version 1.8 of the ACVC contains 2399 tests. When validation testing of TeleGen2 Ada Compiler for VAX/VMS to 1750A was performed, 19 tests had been withdrawn. The remaining 2380 tests were potentially applicable to this validation. The AVF determined that 445 tests were inapplicable to this implementation, and that the 1935 applicable tests were passed by the implementation.

The AVF concludes that the testing results demonstrate acceptable conformity to the Ada Standard.

3.2 SUMMARY OF TEST RESULTS BY CLASS

RESULT	TEST CLASS						TOTAL
	A	B	C	D	E	L	
Passed	66	862	951	15	10	31	1935
Failed	0	0	0	0	0	0	0
Inapplicable	3	5	417	2	3	15	445
Withdrawn	0	7	12	0	0	0	19
TOTAL	69	874	1380	17	13	46	2399

TEST INFORMATION

3.3 SUMMARY OF TEST RESULTS BY CHAPTER

RESULT	CHAPTER												TOTAL
	2	3	4	5	6	7	8	9	10	11	12	14	
Passed	96	222	298	242	159	97	136	262	107	32	217	67	1935
Failed	0	0	0	0	0	0	0	0	0	0	0	0	0
Inapplicable	20	103	122	5	2	0	3	0	23	0	1	166	445
Withdrawn	0	5	5	0	0	1	1	2	4	0	1	0	19
TOTAL	116	330	425	247	161	98	140	264	134	32	219	233	2399

3.4 WITHDRAWN TESTS

The following 19 tests were withdrawn from ACVC Version 1.8 at the time of this validation:

C32114A	C41404A	B74101B
B33203C	B45116A	C87B50A
C34018A	C48008A	C92005A
C35904A	B49006A	C940ACA
B37401A	B4A010C	CA3005A..D (4 tests)
		BC3204C

See Appendix D for the reason that each of these tests was withdrawn.

3.5 INAPPLICABLE TESTS

Some tests do not apply to all compilers because they make use of features that a compiler is not required by the Ada Standard to support. Others may depend on the result of another test that is either inapplicable or withdrawn. For this validation attempt, 445 tests were inapplicable for the reasons indicated:

- C34001D, B52004E, B55B09D, and C55B07B use SHORT_INTEGER which is not supported by this compiler.
- C34001F and C35702A use SHORT_FLOAT which is not supported by this compiler.

- . C52008B declares a record type with four discriminants of type integer and having default values. The type may be used in the declaration of unconstrained objects, but the size of these objects exceeds the maximum object size of this implementation, and `NUMERIC_ERROR` is raised.
- . C55B16A makes use of an enumeration representation clause containing noncontiguous values which is not supported by this compiler.
- . D64005F and D64005G are inapplicable because they make use of nested procedures as subunits to a level of 10 which exceeds the capacity of the compiler.
- . B86001D requires a predefined numeric type other than those defined by the Ada language in package `STANDARD`. There is no such type for this implementation.
- . C86001F redefines package `SYSTEM`, but `TEXT_IO` is made obsolete by this new definition in this implementation and the test cannot be executed since the package `REPORT` is dependent on the package `TEXT_IO`.
- . C87B62B uses a length clause which is not supported by this compiler. The length clause `'STORAGE_SIZE` for access types is rejected during compilation.
- . BA1011C, CA1012A, CA2009C, CA2009F, LA5008A..H (8 tests), LA5008J, LA5008M, LA5008N, and BC3205D compile generic specifications and bodies in separate compilations which is not supported by this compiler.
- . LA5008I and LA5008K are inapplicable because, in this implementation, a generic unit is made obsolete by the recompilation of a unit on which the generic body (but not the specification) depends. Since this implementation does not support separate compilation of generic unit specifications and bodies, a generic specification must be considered obsolete whenever the body is found to be obsolete. These tests should report at link time that the body of a generic unit is obsolete. However, a compile-time error message reports that the generic unit is obsolete.
- . CA3004E, EA3004C, and LA3004A use `INLINE` pragma for procedures which is not supported by this compiler.
- . CA3004F, EA3004D, and LA3004B use `INLINE` pragma for functions which is not supported by this compiler.
- . AE2101C uses an instantiation of package `SEQUENTIAL_IO` with unconstrained array types which is not supported by this compiler.

TEST INFORMATION

- AE2101H uses an instantiation of package `DIRECT_IO` with unconstrained array types which is not supported by this compiler.
- The following 242 tests require a floating-point accuracy that exceeds the maximum of 9 supported by the implementation:

C24113F..Y (20 tests) C35708F..Y (20 tests) C45421F..Y (20 tests)
C35705F..Y (20 tests) C35802F..Y (20 tests) C45424F..Y (20 tests)
C35706F..Y (20 tests) C45241F..Y (20 tests) C45521F..Z (21 tests)
C35707F..Y (20 tests) C45321F..Y (20 tests) C45621F..Z (21 tests)

- The following 164 tests require the use of external files. This implementation supports only the files `STANDARD_INPUT` and `STANDARD_OUTPUT`:

CE2102C	CE3104A	CE3411A
CE2102G	CE3107A	CE3412A
CE2104A..D (4 tests)	CE3108A..B (2 tests)	CE3413A
CE2105A	CE3109A	CE3413C
CE2106A	CE3110A	CE3602A..D (4 tests)
CE2107A..F (6 tests)	CE3111A..E (5 tests)	CE3603A
CE2108A..D (4 tests)	CE3112A..B (2 tests)	CE3604A
CE2109A	CE3114A..B (2 tests)	CE3605A..E (5 tests)
CE2110A..C (3 tests)	CE3115A	CE3606A..B (2 tests)
CE2111A..E (5 tests)	CE3203A	CE3704A..B (2 tests)
CE2111G..H (2 tests)	CE3208A	CE3704D..F (3 tests)
CE2201A..F (6 tests)	CE3301A..C (3 tests)	CE3704M..O (3 tests)
CE2204A..B (2 tests)	CE3302A	CE3706D
CE2210A	CE3305A	CE3706F
CE2401A..F (6 tests)	CE3402A..D (4 tests)	CE3804A..E (5 tests)
CE2404A	CE3403A..C (3 tests)	CE3804G
CE2405B	CE3403E..F (2 tests)	CE3804I
CE2406A	CE3404A..C (3 tests)	CE3804K
CE2407A	CE3405A..D (4 tests)	CE3804M
CE2408A	CE3406A..D (4 tests)	CE3805A..B (2 tests)
CE2409A	CE3407A..C (3 tests)	CE3806A
CE2410A	CE3408A..C (3 tests)	CE3806D..E (2 tests)
AE3101A	CE3409A	CE3905A..C (3 tests)
CE3102B	CE3409C..F (4 tests)	CE3905L
EE3102C	CE3410A	CE3906A..C (3 tests)
CE3103A	CE3410C..F (4 tests)	CE3906E..F (2 tests)

3.6 SPLIT TESTS

If one or more errors do not appear to have been detected in a Class B test because of compiler error recovery, then the test is split into a set of smaller tests that contain the undetected errors. These splits are then compiled and examined. The splitting process continues until all errors are detected by the compiler or until there is exactly one error per split. Any Class A, Class C, or Class E test that cannot be compiled and executed

because of its size is split into a set of smaller subtests that can be processed.

Splits were required for six Class B tests:

BA3006A	BA3006B	BA3007B
BA3008A	BA3008B	BA3013A

3.7 ADDITIONAL TESTING INFORMATION

3.7.1 Prevalidation

Prior to validation, a set of test results for ACVC Version 1.8 produced by the TeleGen2 Ada Compiler for VAX/VMS to 1750A was submitted to the AVF by the applicant for review. Analysis of these results demonstrated that the compiler successfully passed all applicable tests, and that the compiler exhibited the expected behavior on all inapplicable tests.

3.7.2 Test Method

Testing of the TeleGen2 Ada Compiler for VAX/VMS to 1750A using ACVC Version 1.8 was conducted on-site by a validation team from the AVF. The configuration consisted of a MicroVAX II host operating under MicroVMS, Version 4.2, and an ECSP0 SIM50A, Version 4.0. The target simulator was executed on the host computer system.

A magnetic tape containing all tests except for withdrawn tests, tests requiring unsupported floating-point precisions, and tests requiring external files was taken on-site by the validation team for processing. Tests requiring splits during the prevalidation testing were included in their split form on the magnetic tape.

The test tape was read on one of the MicroVAX II computers at TeleSoft. The tests were then written to a TK50 cartridge tape for transfer to one of the three MicroVAX II host computers. The tests were renamed into a directory structure that supports TeleSoft's automated testing command procedures. The same tape and renaming process was performed on the second of the three host computers. A portion of the test suite was copied across a DECnet connection to the third MicroVAX II. The support packages were compiled on one host and copied to the other two machines across the DECnet connection.

After the test files were loaded to disk, the full set of tests was compiled and linked on the MicroVAX II machines, and all executable tests were run on the ECSP0 SIM50A, Version 4.0. Object files were linked on the host computer, and executable images were loaded directly into the simulator. Results were transferred to a Gould computer for printing.

TEST INFORMATION

The compiler was tested using command scripts provided by TeleSoft and reviewed by the validation team. The following options were in effect for testing:

<u>Option</u>	<u>Effect</u>
/MONITOR	Display progress messages that allow the user to monitor the compilation process.
/PROCEED	Cause the compilation to continue after errors without prompting the user for input.
/LIST	Control the error listing output by the compiler. The compiler always outputs all error messages to the device specified by SYS\$OUTPUT. This option allows the user to send the error listing to a file.

Test output, compilation listings, and job logs were captured on magnetic tape and archived at the AVF. The listings examined on-site by the validation team were also archived.

3.7.3 Test Site

The validation team arrived at TeleSoft in San Diego CA on 14 March 1987, and departed after testing was completed on 19 March 1987.

APPENDIX A

DECLARATION OF CONFORMANCE

TeleSoft has submitted the following declaration of conformance concerning the TeleGen? Ada Compiler for VAX/VMS to 1750A.

DECLARATION OF CONFORMANCE


Compiler Implementor: TeleSoft, Inc.
Ada® Validation Facility: ASD/SCOL, Wright-Patterson AFB, OH
Ada Compiler Validation Capability (ACVC) Version: 1.8

Base Configuration

Base Compiler Name: TeleGen2 Ada Compiler for VAX/VMS to 1750A	Version: Release 3.12c
Host Architecture ISA: MicroVAX II	OS&VER #: MicroVMS, Version 4.2
Target Architecture ISA: ECSPO SIM50A Version 4.0	OS&VER #: bare

Implementor's Declaration

I, the undersigned, representing TeleSoft, Inc., have implemented no deliberate extensions to the Ada Language Standard ANSI/MIL-STD-1815A in the compiler listed in this declaration. I declare that TeleSoft, Inc. is the owner of record of the Ada language compiler listed above and, as such, is responsible for maintaining said compiler in conformance to ANSI/MIL-STD-1815A. All certificates and registrations for the Ada language compiler listed in this declaration shall be made only in the owner's corporate name.




TeleSoft, Inc.
Raymond A. Parra, Director, Contracts/Legal

Date: 3/12/82

Owner's Declaration

I, the undersigned, representing TeleSoft, Inc., take full responsibility for implementation and maintenance of the Ada compiler listed above, and agree to the public disclosure of the final Validation Summary Report. I further agree to continue to comply with the Ada trademark policy, as defined by the Ada Joint Program Office. I declare that all of the Ada language compilers listed, and their host/target performance are in compliance with the Ada Language Standard ANSI/MIL-STD-1815A. I have reviewed the Validation Summary Report for the compiler and concur with the contents.



TeleSoft, Inc.
Raymond A. Parra, Director, Contracts/Legal

Date: 3/12/82

APPENDIX B

APPENDIX F OF THE Ada STANDARD

The only allowed implementation dependencies correspond to implementation-dependent pragmas, to certain machine-dependent conventions as mentioned in chapter 13 of MIL-STD-1815A, and to certain allowed restrictions on representation clauses. The implementation-dependent characteristics of the TeleGen2 Ada Compiler for VAX/VMS to 1750A, Release 3.12c, are described in the following sections which discuss topics in Appendix F of the Ada Language Reference Manual (ANSI/MIL-STD-1815A). Implementation-specific portions of the package STANDARD are also included in this appendix.

package STANDARD is

...

type INTEGER is range $-(2^{31})$.. $(2^{31})-1$;

type LONG_INTEGER is range -2_147_483_648 .. 2_147_483_647;

type FLOAT is digits 6 range $-1.93428\text{E}+25$.. $1.93428\text{E}+25$;

type LONG_FLOAT is digits 9 range $-2.12676500\text{E}+37$.. $2.12676500\text{E}+37$;

type DURATION is delta 0.000061 range -86_400.0 .. 86_400.0;

...

end STANDARD;

APPENDIX F

OF THE LANGUAGE REFERENCE MANUAL

The Ada language definition allows for certain target dependencies in a controlled manner. This section, called Appendix F as prescribed in the LRM, describes implementation-dependent characteristics of the TeleGen2 system for VAX/VMS hosts and embedded 1750A targets.

1. Implementation-Defined Pragmas

`pragma INTERFACE(Assembly, <subroutine_name>);`

`pragma INTERFACE(J73_ECSP0, <subroutine_name>);`

`pragma PACK(<type_name>);`

where: <type_name> represents an array or record type which is to be stored in the minimum space.

`pragma INLINE(<subprogram_name>);`

`pragma SUPPRESS(<condition_name> [, on => <name>]);`

where: <condition_name> is one of: `access_check`, `discriminant_check`, `index_check`, `length_check`, `range_check`, `division_check`, `overflow_check`, `elaboration_check`, `storage_check`.

`pragma ELABORATE(<library_unit_name> {, <library_unit_name> });`

Specifies order of elaboration for the mentioned library units.

`pragma PRIORITY (<priority_type>);`

Specifies priority for a task.

<code>Integer'First</code>	<code>-32_768</code>
<code>Integer'Last</code>	<code>32_767</code>
<code>Integer'Width</code>	<code>6</code>
<code>Long_Integer'First</code>	<code>-2_147_483_648</code>
<code>Long_Integer'Last</code>	<code>2_147_483_647</code>
<code>Long_Integer'Width</code>	<code>11</code>
<code>Float'Digits</code>	<code>6</code>
<code>Long_Float'Digits</code>	<code>9</code>

<code>Duration'Delta</code>	<code>.000050</code>
<code>Duration'First</code>	<code>-86_400</code>
<code>Duration'Last</code>	<code>86_400</code>
<code>Priority'First</code>	<code>0</code>
<code>Priority'Last</code>	<code>255</code>

<code>Any_Float'Machine_Rounds</code>	<code>False</code>
<code>Any_Real'Machine_Overflows</code>	<code>True</code>
<code>Any_Float'Machine_Radix</code>	<code>2</code>
<code>Any_Float'Machine_Emin</code>	<code>-128</code>

Any_Float'Machine_Emax	127
Float'Mantissa	21
Long_Float'Mantissa	31

2. Package SYSTEM

The current specification of package SYSTEM is provided below. Note that the named number Tick is not used by any component of the Ada compiler or run-time system. Similarly, Memory_Size is not used. package SYSTEM is

```

type Address is private;
Null_Address : constant Address;

type Physical_Address is private;

type Subprogram_Value is private;

type Name is (TeleSoft_Ada);
System_Name : constant Name := TeleSoft_Ada;

Storage_Unit : constant := 16;
Memory_Size : constant := 65536;

Min_Int : constant := -(2 ** 31);
Max_Int : constant := (2 ** 31) - 1;
Max_Digits : constant := 9;
Max_Mantissa : constant := 31;

Fine_Delta : constant := 1.0 / (2 ** (Max_Mantissa - 1));

Tick : constant := 0.0001;

subtype Priority is Integer range 0..255;

Max_Object_Size : constant := Max_Int;
Max_Record_Count : constant := Max_Int;
Max_Text_Io_Count : constant := Max_Int-1;
Max_Text_Io_Field : constant := 1000;

private

type Address is Access Integer;
Null_Address : constant Address := null;

type Physical_Address is range 16#0#..16#7FFFFFFF#;

type Subprogram_Value is record
  Logical_Address : Target_Logical_Address;
  Address_State : Target_Address_State;

```

```
Static_Base : Target_Logical_Address;  
end record;
```

end SYSTEM;

3. Representation Causes

The TeleGen2-VAX, 1750A system supports the following representation clause:

- Address clauses for objects (LRM 13.5)
- Pragma PACK and record representation clauses (but see Section 6.6.3)
- Storage_Size for tasks, but not for access types.

4. Implementation-Generated Names

There are no implementation-generated names denoting implementation-dependent components. Names generated by the compiler shall not interfere with programmer-defined names.

5. Address Clause Expression Interpretation

Expressions that appear in Address specifications are interpreted as the first storage unit of the object.

6. Unchecked Conversion Restrictions

Unchecked conversions are allowed between types (or subtypes) T1 and T2 provided that:

- (1) They have the same static size.
- (2) They are not unconstrained array types.
- (3) They are not private (unless they are subtypes of or are derived from type SYSTEM.ADDRESS).
- (4) They are not types with discriminants.

7. Implementation-Dependent Characteristics of the I/O Packages

- In Text_IO, the type Count is defined as follows: type Count is range 0..32767;
- In Text_IO, the type Field is defined as follows: subtype Field is integer range 0..1000;

8. Compilation of Generic Units

The declaration, body, and any subunits of a generic unit must be submitted as a single compilation (i.e., must be in the same source file).

9. Restrictions on Machine Code Insertions

Machine code insertions are not supported in this release.

APPENDIX C
TEST PARAMETERS

Certain tests in the ACVC make use of implementation-dependent values, such as the maximum length of an input line and invalid file names. A test that makes use of such values is identified by the extension .TST in its file name. Actual values to be substituted are represented by names that begin with a dollar sign. A value must be substituted for each of these names before the test is run. The values used for this validation are given below.

<u>Name and Meaning</u>	<u>Value</u>
\$BIG ID1 Identifier the size of the maximum input line length with varying last character.	(1..199 => 'A', 200 => '1')
\$BIG ID2 Identifier the size of the maximum input line length with varying last character.	(1..199 => 'A', 200 => '2')
\$BIG ID3 Identifier the size of the maximum input line length with varying middle character.	(1..99 => 'A', 100 => '3', 101..200 => 'A')
\$BIG ID4 Identifier the size of the maximum input line length with varying middle character.	(1..99 => 'A', 100 => '4', 101..200 => 'A')
\$BIG INT LIT An integer literal of value 298 with enough leading zeroes so that it is the size of the maximum line length.	(1..197 => '0', 198..200 => "298")

TEST PARAMETERS

<u>Name and Meaning</u>	<u>Value</u>
\$BIG_REAL_LIT A real literal that can be either of floating- or fixed-point type, has value 690.0, and has enough leading zeroes to be the size of the maximum line length.	(1..194 => '0', 195..200 => "69.0E1")
\$BLANKS A sequence of blanks twenty characters fewer than the size of the maximum line length.	(1..180 => ' ')
\$COUNT_LAST A universal integer literal whose value is TEXT_IO.COUNT'LAST.	32766
\$EXTENDED_ASCII_CHARS A string literal containing all the ASCII characters with printable graphics that are not in the basic 55 Ada character set.	"abcdefghijklmnopqrstuvwxyz" & " !\$%?@[]^`{}~"
\$FIELD_LAST A universal integer literal whose value is TEXT_IO.FIELD'LAST.	1000
\$FILE_NAME_WITH_BAD_CHARS An illegal external file name that either contains invalid characters, or is too long if no invalid characters exist.	"X}}]!/e%#\$^&~Y"
\$FILE_NAME_WITH_WILD_CARD_CHAR An external file name that either contains a wild card character, or is too long if no wild card character exists.	"XYZ*"
\$GREATER_THAN_DURATION A universal real value that lies between DURATION'BASE'LAST and DURATION'LAST if any, otherwise any value in the range of DURATION.	86_401.0
\$GREATER_THAN_DURATION_BASE_LAST The universal real value that is greater than DURATION'BASE'LAST, if such a value exists.	86_401.0

<u>Name and Meaning</u>	<u>Value</u>
\$ILLEGAL_EXTERNAL_FILE_NAME1 An illegal external file name.	"BAD_CHARACTER%^/%"
\$ILLEGAL_EXTERNAL_FILE_NAME2 An illegal external file name that is different from \$ILLEGAL_EXTERNAL_FILE_NAME1.	(1..257 => 'A')
\$INTEGER_FIRST The universal integer literal expression whose value is INTEGER'FIRST.	-2_147_483_648
\$INTEGER_LAST The universal integer literal expression whose value is INTEGER'LAST.	2_147_483_647
\$LESS_THAN_DURATION A universal real value that lies between DURATION'BASE'FIRST and DURATION'FIRST if any, otherwise any value in the range of DURATION.	-86_401.0
\$LESS_THAN_DURATION_BASE_FIRST The universal real value that is less than DURATION'BASE'FIRST, if such a value exists.	-86_401.0
\$MAX_DIGITS The universal integer literal whose value is the maximum digits supported for floating-point types.	9
\$MAX_IN_LEN The universal integer literal whose value is the maximum input line length permitted by the implementation.	200
\$MAX_INT The universal integer literal whose value is SYSTEM.MAX_INT.	2_147_483_647

TEST PARAMETERS

<u>Name and Meaning</u>	<u>Value</u>
<p>\$NAME</p> <p>A name of a predefined numeric type other than FLOAT, INTEGER, SHORT FLOAT, SHORT INTEGER, LONG FLOAT, or LONG INTEGER if one exists, otherwise any undefined name.</p>	<p>LONG_LONG_INTEGER</p>
<p>\$NEG_BASED_INT</p> <p>A based integer literal whose highest order nonzero bit falls in the sign bit position of the representation for SYSTEM.MAX_INT.</p>	<p>16#FFFFFFFFE#</p>
<p>\$NON_ASCII_CHAR_TYPE</p> <p>An enumerated type definition for a character type whose literals are the identifier NON_NULL and all non-ASCII characters with printable graphics.</p>	<p>(NON_NULL)</p>

APPENDIX D

WITHDRAWN TESTS

Some tests are withdrawn from the ACVC because they do not conform to the Ada Standard. The following 19 tests had been withdrawn at the time of validation testing for the reasons indicated. A reference of the form "AI-ddddd" is to an Ada Commentary.

- . C32114A: An unterminated string literal occurs at line 62.
- . B33203C: The reserved word "IS" is misspelled at line 45.
- . C34018A: The call of function G at line 114 is ambiguous in the presence of implicit conversions.
- . C35904A: The elaboration of subtype declarations SFX3 and SFX4 may raise `NUMERIC_ERROR` instead of `CONSTRAINT_ERROR` as expected in the test.
- . B37401A: The object declarations at lines 126 through 135 follow subprogram bodies declared in the same declarative part.
- . C41404A: The values of 'LAST and 'LENGTH are incorrect in the if statements from line 74 to the end of the test.
- . B45116A: `ARRPRIBL1` and `ARRPRIBL2` are initialized with a value of the wrong type--`PRIBOOL_TYPE` instead of `ARRPRIBOOL_TYPE`--at line 41.
- . C48008A: The assumption that evaluation of default initial values occurs when an exception is raised by an allocator is incorrect according to AI-00397.
- . B49006A: Object declarations at lines 41 and 50 are terminated incorrectly with colons, and end case; is missing from line 42.
- . B4A010C: The object declaration in line 18 follows a subprogram body of the same declarative part.

WITHDRAWN TESTS

- . B74101B: The begin at line 9 causes a declarative part to be treated as a sequence of statements.
- . C87B50A: The call of "/"= at line 31 requires a use clause for package A.
- . C92005A: The "/"= for type PACK.BIG_INT at line 40 is not visible without a use clause for the package PACK.
- . C940ACA: The assumption that allocated task TT1 will run prior to the main program, and thus assign SPYNUMB the value checked for by the main program, is erroneous.
- . CA3005A..D (4 tests): No valid elaboration order exists for these tests.
- . BC3204C: The body of BC3204C0 is missing.

END

DATE

FILMED

7-88

Dtic